



L'huile des records du monde

MVX QUAD 4 – SAE 10W-40

Semi synthetic oil for 4 stroke quads engines

USES

Semi-synthetic SAE 10W40 engine oil for 4-stroke quads used under all operating **conditions** (sport, professional or leisure).

Provides specific protection of the gearboxes and oil-immersed clutches (JASO MA2) whilst improving gear shifting.

Exceeds main quads manufacturer's requirements.

MAIN CHARACTERISTICS

		Units	SAE 10W-40
Density	20° C	kg/m ³	868
Kinematic viscosity	40° C	mm ² /s	100
Kinematic viscosity	100° C	mm ² /s	15.0
Viscosity Index			157
Pour Point		° C	-39
Flash Point Cleveland open cup		° C	>200
Dynamic viscosity	-25° C	mPa.s	6200

The data given in this table are typical production values and cannot be considered as specifications.

PROPERTIES & ADVANTAGES

- Specific friction properties provide excellent clutch operation
- Excellent wear protection of the engine and gearbox components for extended service life
- SAE 10W40 viscosity provides a quick oil flow and improves start-ups at cold temperature
- Good detergent/dispersant properties prevent the formation of deposit for a cleaner engine.
- High shear resistance characteristics provide optimal oil stability in service
- Low level of phosphorus for increased protection of catalytic converters

SPECIFICATIONS

JASO MA2

API SL

