



L'huile des records du monde

## BVX R 500 – SAE 75W-80

**100% semi-synthetic high performance oil for manual transmissions**

### USES

Lubrication of modern manual transmissions and drive axles for passenger cars where a SAE 75W-80 grade is recommended by the OEM (especially **Peugeot, Citroen, Renault**).

Particularly recommended for extended course of severe service, any driving conditions (motorway city traffic), any season

### MAIN CHARACTERISTICS

		Units	SAE 75W-80
Density at	20° C	kg/m <sup>3</sup>	882
Kinematic viscosity at	40° C	mm <sup>2</sup> /s	47.5
Kinematic viscosity at	100° C	mm <sup>2</sup> /s	8.6
Viscosity index			161
Pour point		° C	-45
Flash point Cleveland open cup		° C	200

*The data given in this table are typical production values and cannot be considered as specifications.*

### PROPERTIES & ADVANTAGES

**100% semi synthetic** : formulated with half synthetic molecules and half mineral bases

Excellent fluidity at low temperatures

High extreme-pressure properties

Excellent resistance to oxidation allowing an optimal lubrication till the drain

Excellent lubricating protection of the gearbox components. Easier cold weather start-up and energy saving capabilities

### PERFORMANCES

API GL4+

**BVX R 500** exceeds the performances mentioned.

