



L'huile des records du monde

YACCO MAS3

Monograde detergent lubricant

APPLICATIONS

Mineral SAE30 detergent oil with specific additives suitable for gasoline and Diesel engines (including supercharged), used in regular service conditions.

Also adapted to the lubrication of gearboxes, torque converters and hydraulic systems when the manufacturer requires the use of SAE 30 engine oil.

Suitable to a wide range of application: agriculture, garden equipment, marine, transportation, public works...

MAIN CHARACTERISTICS

		Units	MAS3 SAE 30
Density at	20°C	kg/m ³	890
Kinematic viscosity at	40°C	mm ² /s	100
Kinematic viscosity at	100°C	mm ² /s	11,5
Viscosity index			102
Pour Point		° C	- 12
Flash point Cleveland O. C.		° C	240
T.B.N. (Total Base Number)		mgKOH/g	11,4

The data given in this table are typical production values and cannot be considered as specifications.

PROPERTIES & ADVANTAGES

- Highly detergent and dispersant properties allow to keep the engine clean
- Increased anti-wear, anti-oxidant, anti-corrosion properties for an optimal protection of the engine or transmissions.
- Good anti-foam and anti-rust properties
- Excellent shear resistance provides increased stability of the viscosity in service

SPECIFICATIONS

CF/SF

Caterpillar TO-2

Mercedes-Benz MB 228.0

