



L'huile des records du monde

# MULTIP XTRA2

## Extreme pressure Lithium/CALCIUM complex grease

### USES

Extreme pressure sticky grease, insoluble in water. Recommended for ball bearings, joints and various mechanisms. Particularly adapted to heavy loaded and high temperatures applications. Also suitable for use in presence of water or dust.

Large range of application: automotive, motorcycles, marine, farm and public equipment, industrial and off-road vehicles...

### MAIN CHARACTERISTICS

	NLGI 2 Grade
Colour	Green
Drop point	> 180°C
Thickener	Lithium/Calcium
Weld load	315 kg
Base oil viscosity at 40 °c	310 mm <sup>2</sup> /s

The data given in this table are typical production values and cannot be considered as specifications

### PROPERTIES & ADVANTAGES

- Insoluble in water (even boiling water) and steam. Recommended for equipment working outdoor or in presence of water or mud.
- Excellent stickiness allowing long life maintenance
- High extreme pressure properties for heavy loaded applications
- Good anti-wear and anti-rust protection
- Drop point at 180 °c provides increased protection of parts suffering from overheating

### CLASSIFICATION

N.L.G.I. 2

ISO 6743-9 ► ISO-L-XBEFB 2

DIN 51502 ► DIN KP2P-20

APPLICATION RANGE: -20 °c/+140 °c

Keeps its original properties back to normal in case of short exposure to an excess of temperature.

