



L'huile des records du monde

AGRIPRO MULTI 4 – SAE 15W-40

Multifunctional lubricant for agricultural vehicles

USES =

Lubricates the engine (supercharged or not), the transmissions, the hydraulic systems, clutch and immersed brake systems of **agricultural vehicles**.

According to the manufacturers' recommendations, use this product or a specific oil for the engine (TRANSPRO) and a special oil for the hydraulic system and the transmissions (AGRIPRO HJD or AGRIPRO HF 6).

MAIN CHARACTERISTICS =

		Units	SAE 15W-40
Density at	20° C	Kg/m3	876
Kinematic viscosity at	40° C	mm ² /s	101.5
Kinematic at	100° C	mm ² /s	14.0
Viscosity index			140
Pour point		° C	-30
Flash point Cleveland open cup		° C	> 220

The data given in this table are typical values from production and cannot be specifications in any case.

PROPERTIES & ADVANTAGES =

- Outstanding oxidation resistance provides increased oil stability throughout the service fields
- Excellent protection against rust, corrosion and wear
- Friction coefficient adapted to clutches and oil immersed brakes
- Multigrade capabilities maintain an adequate viscosity at hot and cold temperatures

PERFORMANCES =

MULTIFUNCTIONAL (STOU)

John Deere J27 & Ford M2C 159B/C

Massey Ferguson CMS M 1145/M 1144 and M 1139; New Holland 82009201/2/3

TRANSMISSIONS

API GL4 - Allison C4

ENGINE

API CF-4/SF; ACEA E2 HYDRAULICS & UTTO

HV 100 - John Deere J20C; Massey Ferguson M1135

