



L'huile des records du monde

BVX R 200 – SAE 75W-80

High quality mineral oil for manual transmissions

APPLICATIONS

Lubrication of manual transmissions and drive axles of passenger cars where SAE 75W-80 grade is recommended by the OEM (especially **Peugeot, Citroen** and **Renault**).

Provides easier gear shifting at cold and improves fuel economy.

MAIN CHARACTERISTICS

		Units	SAE 75W-80
Density at	20° C	kg/m ³	884
Kinematic viscosity at	40° C	mm ² /s	49
Kinematic viscosity at	100° C	mm ² /s	8
Viscosity index			137
Pour point		° C	-38
Flash point Cleveland open cup		° C	208

The data given in this table are typical production values and cannot be considered as specifications.

PROPERTIES & ADVANTAGES

- High viscosity index for a mineral oil and **maintains protective lubricating film** at high and low temperatures
- Very good anti-wear and anti-corrosion properties
- **Good thermal stability. Excellent lubrication** of the gearbox components even under severe conditions
- Significant reduction of gear noises improving driving comfort
- Improved anti-friction properties to improve gear shifting
- Improves fuel economy and polluting emissions reduction.

PERFORMANCES

API GL-5

BVX R 200 exceeds the above mentioned performances.

