



L'huile des records du monde

# MVX 500 4T – SAE 15W-50

## Semi synthetic oil for 4 stroke motorbike engines

### USES

Perfect lubrication of the engine working under extreme and **severe conditions** and **anytime** in the year.

Lubricates also the integrated gearboxes for a better protection box/ gearing (JASO MA2).

Is convenient to many types of motorbikes (roadsters, city, customs, GT or competition).

### MAIN CHARACTERISTICS

		Units	SAE 15W-50
Density	20° C	kg/m <sup>3</sup>	875
Kinematic viscosity	40° C	mm <sup>2</sup> /s	130
Kinematic viscosity	100° C	mm <sup>2</sup> /s	17.9
Viscosity Index			153
Pour Point		° C	-36
Flash Point Cleveland open cup		° C	> 210
Dynamic viscosity	-20° C	mPa.s	5300

*The data given in this table are typical production values and cannot be considered as specifications.*

### PROPERTIES & ADVANTAGES

Grade SAE 15W50 for an **optimal lubrication at high temperatures to insure the reliability of the engine at high speed.**

Good levels of **detergency** and **dispersivity**

Very good friction properties **preventing the « gear sliding » phenomenon**

Very good protection against **wear**

**Keeps the engine clean** allowing the removal of pollution during the oil drain


**Low volatility** which reduces oil consumption

### HOMOLOGATIONS

### SPECIFICATIONS

JASO MA2

API SL



JASO T903-2006  
PERFORMANCE IS GUARANTEED by  
YACCO S.A.S.

