



L'huile des records du monde

SVX 1000 SNOW 4T – SAE 5W-40

100 % synthetic oil for 4 stroke snowmobile engines

USES

100% synthetic oil specifically developed for use in modern 4 -Stroke snowmobile engines. Outstanding engine protection under extreme operating conditions: professional or recreational use, racing...

Ensures safe operation of oil-immersed clutches.

MAIN CHARACTERISTICS

		Units	SAE 5W-40
Density	20° C	kg/m ³	858
Kinematic viscosity	40° C	mm ² /s	90
Kinematic viscosity	100° C	mm ² /s	15
Viscosity Index			176
Pour Point		° C	-39
Flash Point Cleveland open cup		° C	225
Dynamic viscosity	-30° C	mPa.s	6000

The data given in this table are typical production values and cannot be considered as specifications.

PROPERTIES & ADVANTAGES

- SAE 5W-40 oil grade provides excellent stability at high temperature and instant lubrication at start up.
- 100 % synthetic formula for optimal protection at high temperature and reduction of oil consumption.
- Meets JASO MA2 clutch friction test requirements
- Use of specific viscosity index improvers allowing exceptional shear stability. This keeps the viscosity in service and increases parts protection
- Good detergent/dispersant properties keep engines clean.

SPECIFICATION

API SL
JASO MA2

