



L'huile des records du monde

# YACCO XXAS3-14 SAE 50

## Detergent and monograde oil

### APPLICATIONS

Detergent and monograde mineral oil specifically developed to lubricate supercharged-or-not Diesel engines, used in regular service conditions.

Also suitable for gasoline engines under non severe service conditions.

Well adapted to the lubrication of gear boxes when the manufacturer recommends an SAE 50 engine oil.

### MAIN CHARACTERISTICS

	Units	XXAS3-14 SAE 50
Density at 20°C	kg/m <sup>3</sup>	896
Kinematic viscosity at 40°C	mm <sup>2</sup> /s	204
Kinematic viscosité at 100°C	mm <sup>2</sup> /s	19
Viscosity index		105
Pour Point	° C	- 9
Flash point Cleveland O. C.	° C	250
T.B.N. (Total Base Number)	mgKOH/g	14

*The data given in this table are typical production values and cannot be considered as specifications.*

### PROPERTIES & ADVANTAGES

- Highly detergent and dispersant to keep the engine clean
- Increased anti-wear, anti-oxidant, anti-corrosion and anti-foam properties for an optimal protection of the engine
- Good viscosity stability in service
- High TBN (Total Base Number) to keep optimal engine performances especially when fuel contains a high sulphur level

### SPECIFICATIONS

API CD/SF

