



# VX 600 - SAE 10W-30

Synthetic oil for gasoline and Diesel engines

## USES

Synthetic oil recommended for gasoline and Diesel engines without particle filter (DPF/GPF).  
Universal oil suitable for urban and high rpm motorway use.

### Specifications:

ACEA A3/B3

API SL/CF



## MAIN PHYSICAL DATA

		Methods	Units	10W-30
Density at	20°C	ASTM D4052	kg/m <sup>3</sup>	856
Kinematic viscosity at	40°C	ASTM D445	mm <sup>2</sup> /s	75
Kinematic viscosity at	100°C	ASTM D445	mm <sup>2</sup> /s	11.8
Viscosity index		ASTM D2270		152
Dynamic viscosity at	- 25°	ASTM D5293	mPa·s	5000
Sulphated ash		ASTM D874	% mass	1
Total Base Number (TBN)		ASTM D2896	mgKOH/g	8

*The data given in this table represents typical production values and should not be taken as specifications.*

## PROPERTIES & ADVANTAGES

- ▶ Outstanding stability at high temperatures.
- ▶ Very good detergent/dispersant properties.
- ▶ Maintains its rheological and chemical properties all year round.
- ▶ Extends the service life of the engine.
- ▶ Keeps the engine clean even under severe service conditions.
- ▶ Ensures the engine's original settings are maintained.



 [facebook.com/yaccosas](https://facebook.com/yaccosas)

 [twitter.com/yaccosas](https://twitter.com/yaccosas)

 [youtube.com](https://youtube.com)

