



VX 100 - SAE 10W-30

Superior mineral oil for
gasoline and diesel engines

USES

Specially developed for cars where SAE 10W-30 oil is recommended. Designed for use in all kinds of driving conditions: roads, motorways, urban traffic, etc.

Provides excellent lubrication and year-round protection for turbocharged or naturally aspirated gasoline and diesel engines.

Compatible with cars fitted with a catalytic converter.

Specifications:

API SL/CF
ACEA A3/B4.

MAIN PHYSICAL DATA

	Methods	Units	10W-30
Density at 20°C	ASTM D4052	kg/m ³	862
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	76
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	12
Viscosity index	ASTM D2270		153
Pour point	ASTM D97	°C	-39
Cleveland Open Cup Flash Point	ASTM D92	°C	216
Dynamic viscosity at -25°C	ASTM D5293	mPa·s	5900
HTHS viscosity	CEC L-036-90	mPa·s	3.6
Sulphated ash	ASTM D874	% mass	1.15
Total Base Number (TBN)	ASTM D2896	mgKOH/g	10

The data given in this table represents typical production values and should not be taken as specifications.

PROPERTIES & ADVANTAGES

- ▶ SAE 10W-30 grade, meaning fast lubrication upon start-up.
- ▶ Outstanding detergent and dispersing properties.
- ▶ Enhanced anti-oxidation properties for long-lasting lubrication.
- ▶ Reduces engine wear and fuel consumption.
- ▶ Keeps the engine clean and prevents clogging.
- ▶ Good anti-foam and anti-corrosion properties.



 facebook.com/yaccos

 twitter.com/yaccos

 youtube.com

