

MVX 500 4T - SAE 15W-50

YACCOSYNTH synthetic technology engine oil for 4-stroke motorbike engines

USES

MVX 500 4T 15W50 is a synthetic technology engine oil for 4-stroke motorcycles. Suitable for all types of motorbikes (roadsters, custom, GT and sports bikes). Provides increased protection of the clutch/gear unit (JASO MA2). Improves the reliability of high-revving engines. Provides perfect engine lubrication, even under severe service conditions, all year round.

<u>Specifications:</u> <u>Approvals:</u>

API SN JASO MA2

M033YCO387 MA2 JASO T903:2006

MAIN PHYSICAL DATA

	Methods	Units	15W-50
Density at 20°C	ASTM D4052	kg/m³	874
Kinematic viscosity at 40°C	ASTM D445	mm²/s	132
Kinematic viscosity at 100°C	ASTM D445	mm²/s	18
Viscosity index	ASTM D2270		152
Pour point	ASTM D97	°C	-33
Cleveland Open Cup Flash Point	ASTM D92	°C	226
Dynamic viscosity at -20°C	ASTM D5293	mPa⋅s	6000
HTHS Viscosity	CEC L-036-90	mPa⋅s	4.8
Sulphated ash	ASTM D874	% mass	1.1
Total Base Number (TBN)	ASTM D2896	mgKOH/g	10

The data given in this table represents typical production values and should not be taken as specifications.

PROPERTIES & ADVANTAGES

- ► SAE 15W50 grade provides increased engine protection at high temperatures and reliability under heavy loads.
- ► Good detergent-dispersant properties for a cleaner engine
- ► Specific additives prevent clutch slip.
- ▶ Very good protection of the engine and gearbox against wear.
- ▶ Low volatility means reduced oil consumption.











